

- All metal multidirectional anti-vibration/shock mounts
- Exceptional reliability and long life
- High damping
- No aging
- Corrosion resistant
- Unequalled temperature range : -180°C to +300°C / -290F to 570 F
- Great adaptability/versatility

Specials on request

(material size and number of loops, etc.)

Dimensions are in millimeters. For reference only

SERIES
Materials and finishes (meets RoHS requirements)
CB2000
Cable: stainless steel galvanized available: CBG
Retainer bars: aluminium alloy/ SurTec
Screws: alloy steel/ zinc plate
Inserts: stainless steel
All stainless steel: CBSS
Other materials on request

MODEL	height H (mm)	width W (mm)	weight (kg)
-10	178	210	22,2
-12	216	248	26,3
-15	235	270	28,5

INTERFACES			
fixtures holes D	Bar 1		
	4 through holes ø19mm	4 through holes ø19mm counter-sunk 90°	4 inserts M18
Bar 2			
4 through holes ø19mm	no suffix	not standard	not standard
4 through holes ø19mm counter-sunk 90°	CM	CM2	not standard
4 inserts M18	IM	CIM	IM2

C B 2 0 0 0 - 1 0 C I M

SERIE: CB2000

'Helical' mount from the CB2000 series

MODEL: -10

height: 178mm

width: 210mm

weight: 22,2kg

loops: serie

standard is 08 loops




INTERFACE: CIM

4 through holes ø19mm

counter-sunk 90° in bar 1,

4 inserts M18 in bar 2





TYPICAL SHOCK/VIBRATION SPECIFICATIONS:

- Air** AIR 7306, MIL-E-5400, MIL-C-172, MIL-STD-810
- Ground Forces** GAM EG13A, SEFT 001, MIL-STD-810, VG 9533
- Marine** GAM EG13C, IT25-21/96-31/15-86, MIL-S-167, MIL-S-901, STANAG 042, BV 043.73, BV 044
- Others** GAM EMB1, GAM EMBT4, DEF STAN 07-55, IEC 571, FINABEL 2C